



规格 Type	直径 ØD(mm)	公差 Tol. (mm)	内冷孔径 Ød(mm)	公差 Tol. (mm)	孔中心偏离 a
RRM 0420-3300U1S	4.0	+0.30~+0.50	0.80	± 0.10	0.10
RRM 0520-3300U1S	5.0	+0.30~+0.50	0.80	± 0.10	0.13
RRM 0630-3300U1S	6.0	+0.30~+0.50	1.00	± 0.15	0.15
RRM 0730-3300U1S	7.0	+0.30~+0.60	1.00	± 0.15	0.15
RRM 0830-3300U1S	8.0	+0.30~+0.60	1.00	± 0.15	0.15
RRM 0930-3300U1S	9.0	+0.30~+0.60	1.40	± 0.15	0.20
RRM 1030-3300U1S	10.0	+0.30~+0.60	1.40	± 0.15	0.20
RRM 1130-3300U1S	11.0	+0.30~+0.60	1.40	± 0.15	0.28
RRM 1230-3300U1S	12.0	+0.30~+0.60	1.75	± 0.15	0.30
RRM 1330-3300U1S	13.0	+0.30~+0.70	1.75	± 0.15	0.34
RRM 1430-3300U1S	14.0	+0.30~+0.70	1.75	± 0.15	0.37
RRM 1530-3300U1S	15.0	+0.30~+0.70	2.00	± 0.20	0.40
RRM 1630-3300U1S	16.0	+0.30~+0.70	2.00	± 0.20	0.40
RRM 1730-3300U1S	17.0	+0.30~+0.80	2.00	± 0.20	0.47
RRM 1830-3300U1S	18.0	+0.30~+0.80	2.00	± 0.20	0.50
RRM 1930-3300U1S	19.0	+0.30~+0.80	2.00	± 0.20	0.50
RRM 2040-3300U1S	20.0	+0.30~+0.80	2.50	± 0.25	0.50
RRM 2140-3300U1S	21.0	+0.30~+0.80	2.50	± 0.25	0.50
RRM 2240-3300U1S	22.0	+0.30~+0.80	2.50	± 0.25	0.50
RRM 2340-3300U1S	23.0	+0.30~+0.80	2.50	± 0.25	0.50
RRM 2440-3300U1S	24.0	+0.30~+0.80	3.00	± 0.25	0.50
RRM 2540-3300U1S	25.0	+0.30~+0.80	3.00	± 0.25	0.50
RRM 2640-3300U1S	26.0	+0.30~+0.80	3.00	± 0.25	0.50
RRM 2840-3300U1S	28.0	+0.30~+0.80	3.00	± 0.25	0.50
RRM 3040-3300U1S	30.0	+0.30~+0.80	3.00	± 0.25	0.50
RRM 3240-3300U1S	32.0	+0.30~+0.80	3.00	± 0.25	0.50
RRM 3440-3300U1S	34.0	+0.30~+0.80	3.00	± 0.25	0.50